Quinti®



Direction and advanced armchair form Quinti collection. High level materials, high comfort and strength over time guaranteed. Quinti is Made in Italy Warranty, certified n° 290.058.V.

Base

- 3 types of bases are available:
- 1. Die cast aluminum of 670 mm "Loop" type [standard]
- 2. "Star" base, 4 spokes on feet.
- 3. Cantilever structure, sled base with or without armrests.

Casters

Double tread diam 50 mm, standard or rubberized, both can be free [standard] and self-braking. The feet in polyamide are interchangeable to the casters with the same locking pin at the base.

Elevation

All Quinti's gas columns are in accordance with the DIN 4550 norm and they exceed the fourth level.

Mechanics

M5 The armchair has a tilting single lever mechanism with gas, height and block command in operative position. It has a wheel for the variation of the tilt rigidity. The main body is entirely made out of die-cast aluminum.

M4 [optional] the point of rotation of this mechanism is advanced. The blocking lever allows the blocking process in 3 positions with a backstop system of the seat. It has a wheel for the variation of the tilting rigidity. The main body is entirely made out of die-cast aluminum.

M3 [optional] Tilting Mechanism Plus advanced which allows the regulation of seating height, free tilt of backrest with block on 4 positions. Regulation of tilting tension, shiny aluminum.

 $\boldsymbol{M10}$ [optional] Harmonic mechanism of seat and tilt of 4° permanent.

Armrests

Couplets of armrests in chromed aluminum.


Seat & Backrest

Both made with a monocoque in beech plywood pg 12 mm, adequately upholstered and coverd.

Upholsters

They have a density of 40 and a thickness of 3 cm, adequately upholstered and covered in the 130 colors from the Quinti colours system.

Quinti®







UPHOLSTERY

BIO-EXPO **CATEGORY 2**

300 ar/mt2 100% Propitex FR bacteriostatic Class 1UNI EN ISO 354:2003 100.000 +/- 10% cycles Martindale

EXTREME CATEGORY 2

350 gr/mtl $100\bar{\%}$ Xtreme FR Class 1 , EN 1021-1/2 100.000 +/- 10% cycles Martindale

CATEGORY 2

560 gr/mtl 100% Polyester FR Class 1 80.000+/- 10% cycles Martindale

ECOPELLE CATEGORY 2

630 gr/mt2 83% PVC, 17% Synthetic ISO 379-DIN75200-CSERF4/83 10% cycles Martindale

ERA CATEGORY 3

448 gr/mtl 100% Trevira CS Class 1UNI EN ISO 354:2003 100.000 +/- 10% cycles Martindale

LASER PLUS **CATEGORY 3**

630 gr/mtl 100% Polyester FR Trevira Classe1 , 4.000 +/- cycles Martindale

ECOPELLE SOUL CATEGORY 3

760 gr/mt2 Superficies 100% POLIURETANO. Base Polyester 85%,17% Cotton EN1021-1/BS5852 PART 1 >100.000 EN ISO 5470-2

MELANGE **CATEGORY 3**

390 g/lin.m 100% Trevira CS Class 1 80.000 +/- 10% cycles Martindale

JET **CATEGORY 3**

365+/- 5% g/lin.m 100% Polyester FR Class 1 80.000+/- 10% cycles Martindale

ECOPELLE SISTEMA PRO CATEGORY 3

710 gr/mt2 Surface 93% PVC Base Polyester 28% CLASSE1 100.000 CICLI

ECOPELLE VITAX CATEGORY 3

850 gr/mt2 Surface 98% PVC 2% PU Base cotton 100% CLASSE 1 100.000 CICLI

ONE RECICLE CATEGORY 3

525 gr/mt2 100% recycled polyester Base cotton 100% CLASSE 1IM 100.000 CICLI

LANA **CATEGORY 5**

500 gr/mt2 75% Lana, 25% polyamide 100.000 cycles Martindale

PELLE **CATEGORY 5/6**

620 g/lin.m 100% Cow leather Class 1, EN 1021-1/2

PIED POULE **CATEGORY 6**

550 g/lin.m 66% cotton, 34% Polyester 35.000 % cycles Martindale

EUROPOST 2 CATEGORY 6

710 a/lin.m 63% PU, 16% CO, 21% PL Ini1975 CLASS1emme,UNI9175/FA 50.000% cycles Martindale

PREMIUM /ELEGANCE **CATEGORY 7**

100% First quality cow leather Thickness 1,2/1,4 mm EN1021-1/2

STEELCUT TRIO CATEGORY 7

770 g/lin.m 90% New wool worsted, 10% Nylon Class 1, EN 1021-1/2 100.000 % cycles Martindale

REMIX CATEGORY 7

415 g/lin.m 90% New wool worsted, 10% Nylon Class 1, EN 1021-1/2 100.000 % cycles Martindale

VELLUTO DECONTRACTE **CATEGORY 7**

590 g/lin.m 19% CO, 61% PC,10% PL, 10%VI 40.000 % cycles Martindale

MERIT **CATEGORY 7**

500g/lin.m 76% Polyester Recycled 24% Polyester EN 1021-1/2 85.000 % cycles Martindale

VELLUTO CATEGORY 8

600 g/lin.m 100.000 % PL Flame retardant

PELLE SOFT **CATEGORY 8**

100% Cow leather Thickness,8-2 mm Aniline treatment - First quality EN1021-1/2



USAGE AND CARE

For a proper maintenance of the products and to maintain unchanged the characteristics of the materials, we recommend to follow some very simple care instructions.

FABRICS

Cleaning: check the dedicated selection written on the color Swatch card. Usage: it is recommended to pay attention to the fabrics as they can be easily cut or ripped.

LEATHERS

Cleaning: clean with a white wet cloth with water. We recommend to use high quality products for the cleaning of the leather and to follow carefully the instructions of the manufacturer. In doubt, try out the product on a hidden part and wait at least 24 hours for the occurrence of any problems. Usage: remember that the leather is a delicate material therefore, it is recommended to pay particular attention while using.

WOODS

Cleaning: clean with a soft and wet cloth with warm water. We always recommend to dry immediately after the cleaning process. All liquids or other residue must be removed in order to avoid the absorption. Usage: wooden surfaces, being a natural material, could be affected by an alteration of the color shade during time and use. We also remind that wooden surfaces cannot bear with high temperatures if placed directly on the wooden top.

METALS

Cleaning: both steel or aluminum surfaces, and painted ones, must be cleaned with a soft and wet cloth with hot water. For the most persistent stains, a small amount of liquid soap diluted in water may be used. We always recommend to dry immediately with a soft cloth or a leather one after the cleaning process. Never using cleaning products for steel, chlorine, bleach or other strong detergents. It is not recommended to use abrasive creams, score pads and abrasive sponges that can scratch the metal surfaces. Usage: pay attention to the stains of food such as coffee, coke, fruit juices that can leave indelible marks on the surface.

WARRANTY

QUINTI guarantees the products will maintain their properties for 6 years from delivery, except normal usury and provided that they will be used according to the guidelines given. QUINTI will replace, free of charge, any product found non-compliant with this warranty, without incurring any other liability of sort. Components, external accessories or materials supplied by the buyer and applied to the products in order to customize them will not be supported by the guarantee. For an optimal maintenance of the products and to keep unchanged the characteristics of the materials with which they are made, some simple attentions are necessary.