# **MANTA**



MANTA Lounge armchair is suitable for waiting and contract areas or even as a home armchair.




- 1. No headrest armchair
- 2 . No headrest swinging armchair
- 3 . Headrest armchair4 . Headrest swinging armchair
- 5. Coffee table

L 80/50 P80/57 H 79/46 L 80/50 P95/57 H 77/46 L 80/50 P80/57 H 79/46 L 80/50 P95/57 H 77/46 L 100 P 100 H 34

# **MANTA**



# DIMENSIONS



# STRUCTURE

Available in 5 different bases:

- 4 legs in metal chromed tubular
- Chromed or painted in black metal truss
- 4 legs in solid oak with natural or tempered finish
- 4 spoke self-aligning base on swivelling feet
- Rocking base with metal structure painted in white or black provided with solid oak sleds natural or tempered.

# STRUCTURE AND FOAM

The inner structure of Manta is a metal skeleton provided with elastic belts to increase the comfort, and adequately padded with polyurethanic cold injected foam rubber. The seat cushion is half in rubber and half in memory rubber.

Available even with fireproof castors Certified 1IM.

# ACCESSORIES

- Comfortable headrest applicable in every version.
- Goose down quilt that can be placed on the armchair

- Wide coffee table in metal chromed truss or painted in black with a natural, tempered or marble oak plan.

# <u>MANTA</u>

## UPHOLSTERY

#### BIO-EXPO

CATEGORY 2 300 gr/mt2 100% Propitex FR bacteriostatic Class 1UNI EN ISO 354:2003 100.000 +/- 10% cycles Martindale

### EXTREME

CATEGORY 2 350 gr/mtl 100% Xtreme FR Class 1 , EN 1021-1/2 100.000 +/- 10% cycles Martindale

#### LASER

CATEGORY 2 560 gr/mtl 100% Polyester FR Class 1 80.000+/- 10% cycles Martindale

#### ECOPELLE CATEGORY 2

CA LEGORY 2 630 gr/mt2 83% PVC, 17% Synthetic ISO 379-DIN75200-CSERF4/83 10% cycles Martindale

## ERA

CATEGORY 3 448 gr/mtl 100% Trevira CS Class 1UNI EN ISO 354:2003 100.000 +/- 10% cycles Martindale

#### LASER PLUS

CATEGORY 3 630 gr/mtl 100% Polyester FR Trevira Classe1 , 4.000 +/- cycles Martindale

ECOPELLE SOUL CATEGORY 3 760 gr/mt2 Superficies 100% POLIURETANO, Base Polyester 85%,17% Cotton EN1021-1/BS5852 PART 1 >100.000 EN ISO 5470-2 MELANGE CATEGORY 3 390 g/lin.m 100% Trevira CS Class 1 80.000 +/- 10% cycles Martindale

#### JET CATEGORY 3

365+/- 5% g/lin.m 100% Polyester FR Class 1 80.000+/- 10% cycles Martindale

ECOPELLE SISTEMA PRO CATEGORY 3

710 gr/mt2 Surface 93% PVC Base Polyester 28% CLASSE1 100.000 CICLI

#### ECOPELLE VITAX CATEGORY 3

850 gr/mt2 Surface 98% PVC 2% PU Base cotton 100% CLASSE 1 100.000 CICLI

#### ONE RECICLE

CATEGORY 3 525 gr/mt2 100% recycled polyester Base cotton 100% CLASSE 1IM 100.000 CICLI

LANA CATEGORY 5 500 gr/mt2 75% Lana, 25% polyamide Class 1 100.000 cycles Martindale

PELLE CATEGORY 5/6 620 g/lin.m 100% Cow leather Class 1, EN 1021-1/2

PIED POULE CATEGORY 6 550 g/lin.m 66% cotton, 34% Polyester 35.000 % cycles Martindale

# Quinti®

#### EUROPOST 2 CATEGORY 6

710 g/lin.m 63% PU, 16% CO, 21% PL Ini1975 CLASS1emme,UNI9175/FA 50.000% cycles Martindale

PREMIUM /ELEGANCE CATEGORY 7 100% First quality cow leather Thickness 1,2/1,4 mm EN1021-1/2

STEELCUT TRIO CATEGORY 7 770 g/lin.m 90% New wool worsted, 10% Nylon Class 1, EN 1021-1/2 100.000 % cycles Martindale

REMIX CATEGORY 7 415 g/lin.m 90% New wool worsted, 10% Nylon Class 1, EN 1021-1/2 100.000 % cycles Martindale

VELLUTO DECONTRACTE' CATEGORY 7 590 g/lin.m 19% CO, 61% PC,10% PL, 10%VI 40.000 % cycles Martindale

MERIT CATEGORY 7 500g/lin.m 76% Polyester Recycled 24% Polyester EN 1021-1/2 85.000 % cycles Martindale

VELLUTO CATEGORY 8 600 g/lin.m 100.000 % PL Flame retardant

PELLE SOFT CATEGORY 8 100% Cow leather Thickness,8-2 mm Aniline treatment – First quality EN1021-1/2

# MANTA



## USAGE AND MAINTENANCE

In order to have an optimal maintenance of the products and to preserve the characteristics of the materials by which they are made, it is recommended the following course of action.

#### FABRICS

Cleaning: check the dedicated selection written on the color Swatch card.

Usage: it is recommended to pay careful attention to the fabrics as they can be cut or ripped easly.

#### WOODS

Cleaning: clean using a soft cloth, soaked in tepid water. Dry always after the cleaning. Remove immediately any liquid substances or other residue in order to prevent the absorption.

Usage: wooden surfaces, being a natural material, might be subjected to color alterations with sun exposure and use over time. It is reminded that wooden surfaces cannot endure direct heat sources.

#### METALS

Cleaning: both steel and aluminum surfaces, and the painted ones, have to be cleaned using a soft cloth soaked in tepid water. For the most persistent stains it is possible to dilute mild soap with water moderately. Dry always after the cleaning, using a soft cloth o deer-hide. Do not use cleaning products for steel, chlorine, bleach or other strong products. It is not recommended to use abrasive, scourers, which can scratch the metal surfaces.

Usage: pay attention to the food stains as coffee, coke, fruit juices that can make indelible marks on the surfaces.

#### WARRANTY

QUINTI guarantees the products will maintain their properties for 6 years from delivery, except normal usury and provided that they will be used according to the guidelines given. QUINTI will replace, free of charge, any product found non-compliant with this warranty, without incurring any other liability of sort. Components, external accessories or materials supplied by the buyer and applied to the products in order to customize them will not be supported by the guarantee. For an optimal maintenance of the products and to keep unchanged the characteristics of the materials with which they are made, some simple attentions are necessary.