

MEGA is a seat system featured with a contemporary design and limitless compositive ways. Moduls are provided with metal legs and beam. The chance to insert wood plans and metal coffee tables give maximum functionality and versatility.



MEGA may be limitless combined and made out of:


- 1. Straightforward seat element with or without backrest
- 2. A 90° curved element with or without backrests
- 3. A 45 ° curved element without backrests (available with the backrest only on the straight part)
- 4. Support surface element in natural oak wood.
- 5. Support surface in painted steel, which has to be anchored to the linear beam in the central part. Backrests can be assembled in both sides in the linear version.







DIMENSIONS



STRUCTURE

The MEGA system structure is entirely made out of white painted steel RAL 9003, anthracite 7016 coral RA3016.

Made up of a 80x40 beam, legs are created with a 30 diameter tubular and steel plate of 2mm of thickness and adjustable feet.

STRUCTURE AND FOAM

The seat cushion is made out of expanded polyurethanic and cushproof rubber with a density of 40 and 8cm of thickness, laid on wood support of 15 mm of thickness.

The backrests are made out of polyurethanic cold injected foam rubber with and steel.

Available even with fireproof castors Certified 1IM.

ACCESSORIES

- Coffee table in oak-veneered wood painted in temperate or natural which can be inserted in place of a seat.
 - With rounded angles and 25mm of thickness.
- Support surface in painted steel, which has to be anchored to the beam.





$\underline{MEGA} \text{ Archirivolto Design}$



EXAMPLES OF MODULARITY





UPHOLSTERY

BIO-EXPO CATEGORY 2

300 gr/mt2 100% Propitex FR bacteriostatic Class 1UNI EN ISO 354:2003 100.000 +/- 10% cycles Martindale

EXTREME CATEGORY 2

350 gr/mtl 100% Xtreme FR Class 1 , EN 1021-1/2 100.000 +/- 10% cycles Martindale

LASER CATEGORY 2

560 gr/mtl 100% Polyester FR Class 1 80.000+/- 10% cycles Martindale

ECOPELLE CATEGORY 2

630 gr/mt2 83% PVC, 17% Synthetic ISO 379-DIN75200-CSERF4/83 10% cycles Martindale

ERA CATEGORY 3

448 gr/mtl 100% Trevira CS Class 1UNI EN ISO 354:2003 100.000 +/- 10% cycles Martindale

LASER PLUS CATEGORY 3

630 gr/mtl 100% Polyester FR Trevira Classe1 , 4.000 +/- cycles Martindale

ECOPELLE SOUL CATEGORY 3

760 gr/mt2 Superficies 100% POLIURETANO, Base Polyester 85%,17% Cotton EN1021-1/BS\$852 PART 1 >100.000 EN ISO 5470-2

MELANGE CATEGORY 3

390 g/lin.m 100% Trevira CS Class 1 80.000 +/- 10% cycles Martindale

JET CATEGORY 3

365+/- 5% g/lin.m 100% Polyester FR Class 1 80.000+/- 10% cycles Martindale

ECOPELLE SISTEMA PRO CATEGORY 3

710 gr/mt2 Surface 93% PVC Base Polyester 28% CLASSE1 100.000 CICLI

ECOPELLE VITAX CATEGORY 3

850 gr/mt2 Surface 98% PVC 2% PU Base cotton 100% CLASSE 1 100.000 CICLI

ONE RECICLE CATEGORY 3

525 gr/mt2 100% recycled polyester Base cotton 100% CLASSE 1IM 100.000 CICLI

LANA CATEGORY 5

500 gr/mt2 75% Lana, 25% polyamide Class 1 100.000 cycles Martindale

PELLE CATEGORY 5/6

620 g/lin.m 100% Cow leather Class 1, EN 1021-1/2

PIED POULE CATEGORY 6

550 g/lin.m 66% cotton, 34% Polyester 35.000 % cycles Martindale

EUROPOST 2 CATEGORY 6

710 g/lin.m 63% PU, 16% CO, 21% PL Ini1975 CLASS1emme,UNI9175/FA 50.000% cycles Martindale

PREMIUM /ELEGANCE CATEGORY 7

100% First quality cow leather Thickness 1,2/1,4 mm EN1021-1/2

STEELCUT TRIO CATEGORY 7

770 g/lin.m 90% New wool worsted, 10% Nylon Class 1, EN 1021-1/2 100.000 % cycles Martindale

REMIX CATEGORY 7

415 g/lin.m 90% New wool worsted, 10% Nylon Class 1, EN 1021-1/2 100.000 % cycles Martindale

VELLUTO DECONTRACTE' CATEGORY 7

590 g/lin.m 19% CO, 61% PC,10% PL, 10%VI 40.000 % cycles Martindale

MERIT CATEGORY 7

CATEGORY 7 500g/lin.m 76% Polyester Recycled 24% Polyester EN 1021-1/2 85.000 % cycles Martindale

VELLUTO CATEGORY 8

600 g/lin.m 100.000 % PL Flame retardant

PELLE SOFT CATEGORY 8

100% Cow leather Thickness,8-2 mm Aniline treatment – First quality EN1021-1/2



USAGE AND MAINTENANCE

In order to have an optimal maintenance of the products and to preserve the characteristics of the materials by which they are made, it is recommended the following course of action.

FABRICS

Cleaning: check the dedicated selection written on the color Swatch card.

Usage: it is recommended to pay careful attention to the fabrics as they can be cut or ripped easly.

WOODS

Cleaning: clean using a soft cloth, soaked in tepid water. Dry always after the cleaning. Remove immediately any liquid substances or other residue in order to prevent the absorption.

Usage: wooden surfaces, being a natural material, might be subjected to color alterations with sun exposure and use over time. It is reminded that wooden surfaces cannot endure direct heat sources.

METALS

Cleaning: both steel and aluminum surfaces, and the painted ones, have to be cleaned using a soft cloth soaked in tepid water. For the most persistent stains it is possible to dilute mild soap with water moderately. Dry always after the cleaning, using a soft cloth o deer-hide. Do not use cleaning products for steel, chlorine, bleach or other strong products. It is not recommended to use abrasive, scourers, which can scratch the metal surfaces.

Usage: pay attention to the food stains as coffee, coke, fruit juices that can make indelible marks on the surfaces.

WARRANTY

QUINTI guarantees the products will maintain their properties for 6 years from delivery, except normal usury and provided that they will be used according to the guidelines given. QUINTI will replace, free of charge, any product found non-compliant with this warranty, without incurring any other liability of sort. Components, external accessories or materials supplied by the buyer and applied to the products in order to customize them will not be supported by the guarantee. For an optimal maintenance of the products and to keep unchanged the characteristics of the materials with which they are made, some simple attentions are necessary.